



QUALITY MARINE HARDWARE, EQUIPMENT, AND ACCESSORIES

The publication of this catalog marks the latest in Garhauer block design and manufacture. Because every boat is as different as the people who sail them, and every sailor has a different idea of what hardware best meets their needs, Garhauer offers sailboat blocks in 2 different main types of construction: Unibody Standard Blocks and Unibody Ultra Blocks.

**What the “Series” designations mean:**

<u>SERIES</u>	<u>SERIES 15</u>	<u>SERIES 20</u>	<u>SERIES 25</u>	<u>SERIES 27</u>	<u>SERIES 30</u>	<u>SERIES 40</u>	<u>SERIES 50</u>	<u>SERIES 60</u>	<u>SERIES 70</u>
Maximum line size	5/16"	5/16"	3/8"	3/8"	1/2"	1/2"	5/8"	5/8"	3/4"
Sheave diameter	1"	1-3/4"	2"	2-1/4"	2-1/2"	2-1/2"	3"	3-1/4"	4-1/4"
Safe working load	400 lbs.	600 lbs.	1,150 lbs.	2,000 lbs.	2,400 lbs.	2,800 lbs.	3,000 lbs.	3,500 lbs.	5,000 lbs.

**Please note:** the recommendations above are for normal usage.

If you plan to use these blocks in exceptionally high load areas, we recommend switching to the next higher series of blocks.

**UNIBODY STANDARD BLOCKS:** Are one-piece construction and come in 3 finishes to cosmetically match the other blocks on your boat. Unibody design means that the cheeks to support the sheaves along the outer edge, to distribute the total load more evenly across a larger surface. The absence of fasteners results in superior corrosion resistance. Available in your choice of 3 finishes to match existing hardware on your boat:

**“US”** are blocks with a polished stainless steel surface.

**“USHL”** are blocks with a polished stainless steel surface, specially built to withstand high load conditions. The working loads of these blocks are displayed on the pages they appear.

**“USE”** are blocks with a polished stainless steel surface, built for light load conditions. The working loads of these blocks are displayed on the pages they appear.

**“UAB”** are blocks anodized with a black aluminum surface.

**“UABE”** are blocks with a black aluminum surface, built for light load conditions. The working loads of these blocks are displayed on the pages they appear.

**“UAG”** are blocks anodized with a grey aluminum surface.

**“UAGE”** are blocks with a grey aluminum surface, built for light load conditions. The working loads of these blocks are displayed on the pages they appear.

**UNIBODY ULTRA BLOCKS:** Using the most advanced materials and production techniques, Garhauer has come up with what we believe to be the greatest value in a lightweight, ultra high strength, corrosion-resistant block.

Designated **“UB”**, Garhauer Unibody Ultra Blocks are precision milled from a solid block of premium 6061 T-6 aluminum for high strength to weight ratio. All mating surfaces are constructed with non-conductive Delrin, the longest wear engineering grade plastic. Torlon ball bearings for durable, effortless rotation. The the absence of fasteners results in superior corrosion resistance.

Garhauer Marine was founded in 1970 by two machinist friends who shared a common passion for sailing. Guido Gargiulo and Bill Felgenhauer set up shop in the foothills of the San Bernardino mountains in Southern California. Besides being talented designers, they showed an understanding of sound business decisions when they negotiated a flexible rent on their first shop that was 15 percent of each months’ gross income. As income increased, so did the number of products and need for shop space, eventually expanding to the 12,000 square feet occupied today. Garhauer has a total of five buildings, all adjoining the original shop in the same industrial park in Upland, CA

Well positioned geographically, in what was in the 1970s the center of the burgeoning Southern California fiberglass sailboat industry, Garhauer soon became a respected supplier of marine hardware. Sailboats made by Cal, Oday, Pearson, Islander and Catalina, all included marine hardware built by Garhauer.

Family owned and operated, Garhauer is first and foremost a sailors’ company. Both founders and three generations of their families come to work each morning. Among them are no less than four sailboat owners, whose vessels offer unique real world “test labs”. This real world experience is clearly the best way for Garhauer to prove and improve new designs before offering them in this catalog. The constant obsession with innovation and improvement of the product has been the backbone for growth since day one.

Always innovative in terms of design in marine hardware, Garhauer was not immune to the pricing pressures of domestic manufacturers. Seeking to get a handle on labor costs and reduce dependence on outside vendors, Garhauer invested in the huge productivity gains made possible by computers in general, and computer aided manufacture in particular. 1998 saw the installation of the first automated CNC mill and lathe manufacturing unit, capable of producing complex parts 24/7. These machines now number six and have eliminated traditionally labor intensive operations such as dies and punch press. 2005 saw the installation of Bill’s “dream machine”, the room-sized laser metal cutter. This marvel will cut 5 by 10 foot sheets of aluminum or stainless steel up to 1/4 inch thick with digital accuracy and smooth the edge in one amazingly fast operation.

The robotic machines not only produce absolutely consistent high quality parts for the customer, but also they have greatly aided the design process. What once took a skilled machinist 2 days to prototype, can now largely be completed in 2 hours. All this results in better new designs in the customers hands sooner than ever before.

By functioning in a supplier capacity to larger companies, Garhauer learned the lessons of maintaining low overhead and containment of production costs in order to deliver parts with a competitive cost advantage. Most of the hardware available to all customers was developed and produced using stringent price considerations. All this leads to the same advantage built into every Garhauer part sold to every customer: **Value.**

***Dollar for dollar, absolutely the best marine hardware you can buy anywhere.***



# TABLE OF CONTENTS

METRIC CONVERSION TABLE .....	SEE INSIDE BACK COVER
-------------------------------	-----------------------

## MULTI-USE MARINE BLOCKS

### **FIDDLE BLOCKS**

WITH ADJUSTABLE SHACKLE .....	1,2
WITH BECKET AND ADJUSTABLE SHACKLE .....	3,4
WITH SNAP SHACKLE .....	5
WITH BECKET AND SNAP SHACKLE .....	6
WITH CAM CLEAT AND ADJUSTABLE SHACKLE .....	7
WITH BECKET, CAM CLEAT, AND ADJUSTABLE SHACKLE .....	8,9
WITH CAM CLEAT AND SNAP SHACKLE .....	9
WITH BECKET, CAM CLEAT AND SNAP SHACKLE .....	10

### **SINGLE BLOCKS**

WITH ADJUSTABLE SHACKLE .....	11, 12
WITH BECKET AND ADJUSTABLE SHACKLE .....	13, 14
WITH SNAP SHACKLE .....	15, 16
WITH BECKET AND SNAP SHACKLE .....	17, 18
WITH CAM CLEAT .....	26

### **DOUBLE BLOCKS**

WITH ADJUSTABLE SHACKLE .....	19
WITH BECKET AND ADJUSTABLE SHACKLE .....	20

### **TRIPLE BLOCKS**

WITH ADJUSTABLE SHACKLE .....	21
WITH BECKET AND ADJUSTABLE SHACKLE .....	22
WITH BECKET AND CAM CLEAT ADJUSTABLE SHACKLE .....	23

## SPECIALIZED MARINE BLOCKS

### **UNIBODY SINGLE BLOCKS**

WITH ADJUSTABLE SHACKLE .....	24
WITH BECKET AND ADJUSTABLE SHACKLE .....	24
WITH SWIVEL STAND-UP DECK PLATE .....	35

### **UNIBODY DOUBLE BLOCKS**

WITH ADJUSTABLE SHACKLE .....	25
WITH BECKET AND ADJUSTABLE SHACKLE .....	25

### **SNATCH BLOCKS** .....

### **SWIVEL JAM**

WITH DECK MOUNT .....	26
WITH DECK MOUNT AND FAIR LEAD .....	26

### **VANGS**

BOOM VANGS .....	27, 28
TWO SPEED VANGS .....	28

## DECK BLOCKS AND HARDWARE

HALYARD LIFT BLOCKS .....	29
BOW ROLLERS .....	29
STEM FITTING .....	29
STAINLESS HINGE .....	29
ROPE CLUTCHES .....	30
TABLE MOUNT .....	30
CHEEK BLOCKS .....	31
DECK ORGANIZERS .....	32
FOOT BLOCKS .....	33, 34
CLUTCH FOOT BLOCKS .....	34

### **SINGLE DECK BLOCKS**

WITH SWIVEL STAND-UP DECK PLATE .....	35, 36
WITH BECKET AND SWIVEL STAND-UP DECK PLATE .....	37, 38

## MAST BLOCKS AND HARDWARE

MAST PLATES .....	39
MAST EXIT BLOCKS .....	40
MAST SHEAVES .....	40
MAST BLOCKS .....	40
JAM CLEATS .....	40
BACKSTAY BLOCKS .....	41
STAY ADJUSTERS .....	41
SHACKLES .....	41
"D" SHACKLES .....	41

## BOOM HARDWARE & CONTROL BLOCKS

BOOM BALES .....	42
PRISM POLISH .....	42
BOOM TANGS .....	42
STAY ANCHOR .....	42
EYE STRAPS .....	42
RIGID BOOM VANGS .....	45

## TRACK BLOCKS AND ACCESSORIES

MAINSHEET TRAVELERS .....	43, 44
UNIVERSAL TRAVELER RISERS .....	44
E-Z GLIDE ADJUSTABLE GENOA CAR SYSTEM .....	46
E-Z GLIDE SWIVEL CAM .....	46
TRACK CAR SINGLE BLOCKS .....	46, 47
LOW LEAD CARS .....	48
"T"-TRACK .....	48
TRACK CAR SLIDES .....	49
TRACK CAR ROPE CLUTCH .....	49
TRACK CAR MIDSHIP CLEATS .....	49
GENOA TRACK LADDER .....	49

## TRANSOM & DECK HARDWARE AND ACCESSORIES

STANCHIONS AND GATES .....	50
STANCHION BLOCKS .....	51
STANCHION SWIVEL BLOCKS .....	51
STANCHION SINGLE BLOCKS .....	51
STANCHION DOUBLE BLOCKS .....	51
STANCHION MOUNTED CLEAT .....	51
KAYAK RACKS .....	51
LIFTING DAVITS .....	52
STAINLESS FLAGPOLE STAFF .....	52
LOWER BALL MOUNT .....	52
UPPER SUPPORT RING .....	52
OUTBOARD MOTOR LOCKS .....	52
CARBINER .....	52
RETRACTABLE MOTOR MOUNT .....	52
RADAR TOWERS AND ACCESSORIES .....	53
DINGHY DAVITS AND ACCESSORIES .....	54
TURNBUCKLES .....	55
PINTLES .....	55
GUDGEONS .....	55

# **FIDDLE BLOCKS**

WITH

## **ADJUSTABLE SHACKLE**

### **25-01 US**

length 5-3/4"      width 2"  
weight 8 oz.      shackle 3/16"

### **27-01 US**

length 7-1/4"      width 2-3/8"  
weight 11 oz.      shackle 1/4"

### **30-01 US**

length 7-3/8"      width 2-9/16"  
weight 9oz.      shackle 1/4"

### **35-01 US**

length 8-3/4"      width 3"  
weight 19oz.      shackle 5/16"  
Safe working load: 2800lbs.

### **40-01 US**

length 8"      width 3-7/8"  
weight 18oz.      shackle 5/16"

### **45-01 US**

length 11-1/4"      width 4-1/2"  
weight 50oz.      shackle 3/8"  
Safe working load: 2800lbs.

### **50-01 US**

length 10-1/2"      width 4-5/8"  
weight 37oz.      shackle 1/2"

### **70-01 US**

length 13"      width 6"  
weight 75oz.      shackle 5/8"

**25-01 US**



**27-01 US**



**30-01 US**



**35-01 US**



**40-01 US**



**45-01 US**



**70-01 US**



**50-01 US**





**40-01 UAB**



**30-01 UAB**



**25-01 UAB**



**30-01 UAG**



**35-01 UAGE**



**40-01 UAG**



**25-01 UAG**



## ***FIDDLE BLOCKS*** **WITH** ***ADJUSTABLE*** ***SHACKLE***

### ***25-01 UAB***

length 5-3/4" width 2"  
weight 5oz. shackle 3/16"

### ***30-01 UAB***

length 7-3/8" width 2-9/16"  
weight 9oz. shackle 1/4"

### ***40-01 UAB***

length 8" width 3-7/8"  
weight 15oz. shackle 5/16"

### ***25-01 UAG***

length 5-3/4" width 2"  
weight 5oz. shackle 3/16"

### ***30-01 UAG***

length 7-3/8" width 2-9/16"  
weight 9oz. shackle 1/4"

### ***35-01 UAGE***

length 8" width 2-7/8"  
weight 14oz. shackle 3/16"  
Safe working load: 2000lbs.

### ***40-01 UAG***

length 8" width 3-7/8"  
weight 15oz. shackle 5/16"

# **FIDDLE BLOCKS**

WITH  
**BECKET**  
AND  
**ADJUSTABLE**  
**SHACKLE**

## **25-02 US**

length 6-5/8"      width 2"  
weight 6.5oz.      shackle 3/16"

## **30-02 US**

length 8-1/2"      width 2-9/16"  
weight 12oz.      shackle 1/4"

## **40-02 US**

length 9-1/2"      width 3-13/16"  
weight 18oz.      shackle 5/16"

## **45-02 US**

length 12-3/4"      width 4-1/2"  
weight 52oz.      shackle 3/8"  
Safe working load: 2800lbs.

## **50-02 US**

length 11-1/2"      width 4-5/8"  
weight 2lb.14oz.      shackle 1/2"

## **70-02 US**

length 15"      width 6"  
weight 4lb.14oz.      shackle 5/8"

**25-02 US**



**30-02 US**



**40-02 US**



**45-02 US**



**50-02 US**



**70-02 US**





# ***FIDDLE BLOCKS WITH BECKET AND ADJUSTABLE SHACKLE***

**40-02 UAB**



**30-02 UAB**



**25-02 UAB**



**40-02 UAG**



**30-02 UAG**



**25-02 UAG**



## **25-02 UAB**

length 6-5/8" width 2"  
weight 6oz. shackle 3/16"

## **30-02 UAB**

length 8-1/2" width 2-9/16"  
weight 9oz. shackle 1/4"

## **40-02 UAB**

length 9-1/2" width 3-13/16"  
weight 15oz. shackle 5/16"

## **25-02 UAG**

length 6-5/8" width 2"  
weight 6oz. shackle 3/16"

## **30-02 UAG**

length 8-1/2" width 2-9/16"  
weight 9oz. shackle 1/4"

## **40-02 UAG**

length 9-1/2" width 3-13/16"  
weight 15oz. shackle 5/16"

# FIDDLE BLOCKS

WITH  
**SNAP  
SHACKLE**

## 25-03 US

length 6-3/8" width 2"  
weight 8oz. shackle 1/4"

## 30-03 US

length 8-1/2" width 2-9/16"  
weight 13oz. shackle 5/16"

## 40-03 US

length 9-1/2" width 3-7/8"  
weight 19oz. shackle 5/16"

## 50-03 US

length 10-1/2" width 4-5/8"  
weight 35oz. shackle 3/8"

## 25-03 UAB

length 6-3/8" width 2"  
weight 6oz. shackle 1/4"

## 30-03 UAB

length 8-3/8" width 2-9/16"  
weight 9oz. shackle 5/16"

## 40-03 UAB

length 9-1/2" width 3-7/8"  
weight 16oz. shackle 5/16"

## 25-03 UAG

length 6-3/8" width 2"  
weight 6oz. shackle 1/4"

## 30-03 UAG

length 8-1/2" width 2-9/16"  
weight 9oz. shackle 1/4"

## 40-03 UAG

length 9-1/2" width 3-7/8"  
weight 16 oz. shackle 5/16"

25-03 US



30-03 US



40-03 US



50-03 US



40-03 UAB



30-03 UAB



25-03 UAB



30-03 UAG

25-03 UAG



40-03 UAG





25-04 US



30-04 US



40-04 US



50-04 US



40-04 UAB



30-04 UAB



25-04 UAB



40-04 UAG



30-04 UAG



25-04 UAG



# ***FIDDLE BLOCKS***

WITH

# ***BECKET***

AND

# ***SNAP SHACKLE***

**25-04 US**

length 7-1/8" width 2"  
weight 7.5oz. shackle 3/16"

**30-04 US**

length 9-1/2" width 2-9/16"  
weight 14oz. shackle 1/4"

**40-04 US**

length 9-3/4" width 3-13/16"  
weight 19oz. shackle 5/16"

**50-04 US**

length 11-3/4" width 4-5/8"  
weight 47oz. shackle 1/2"

**25-04 UAB**

length 7-1/8" width 2"  
weight 7oz. shackle 3/16"

**30-04 UAB**

length 8-3/4" width 2-9/16"  
weight 10oz. shackle 1/4"

**40-04 UAB**

length 9-3/4" width 3-13/16"  
weight 16oz. shackle 5/16"

**25-04 UAG**

length 7-1/8" width 2"  
weight 7oz. shackle 3/16"

**30-04 UAG**

length 8-3/4" width 2-9/16"  
weight 10oz. shackle 1/4"

**40-04 UAG**

length 9-3/4" width 3-13/16"  
weight 16oz. shackle 5/16"

# **FIDDLE BLOCKS**

WITH  
**CAM CLEAT**  
AND  
**ADJUSTABLE  
SHACKLE**

## **25-05 US**

length 5-1/2"      width 4"  
weight 12oz.      shackle 3/16"

## **30-05 US**

length 7-1/2"      width 4-1/2"  
weight 18oz.      shackle 1/4"

## **40-05 US**

length 8-1/8"      width 5-1/2"  
weight 23oz.      shackle 5/16"

## **25-05 UAB**

length 5-1/2"      width 4"  
weight 10oz.      shackle 3/16"

## **30-05 UAB**

length 7-1/2"      width 4-3/4"  
weight 14oz.      shackle 1/4"

## **40-05 UAB**

length 8"      width 5-1/2"  
weight 19oz.      shackle 5/16"

## **25-05 UAG**

length 5-1/2"      width 4"  
weight 10oz.      shackle 3/16"

## **30-05 UAG**

length 7-1/2"      width 4-3/4"  
weight 14oz.      shackle 1/4"

## **40-05 UAG**

length 8-1/8"      width 5-1/2"  
weight 19oz.      shackle 5/16"





# ***FIDDLE BLOCKS*** WITH ***BECKET,*** ***CAM CLEAT*** AND ***ADJUSTABLE*** ***SHACKLE***



**25-06 US**



**27-06 US**



**30-06 US**



**35-06 US**



**40-06 US**



**40-06 UAB**



**30-06 UAB**



**25-06 UAB**

**25-06 US**  
length 6-3/4" width 4"  
weight 12oz. shackle 3/16"

**27-06 US**  
length 8-3/8" width 4"  
weight 16oz. shackle 3/16"

**30-06 US**  
length 8-1/2" width 4-1/2"  
weight 18oz. shackle 1/4"

**35-06 US**  
length 10" width 4-5/8"  
weight 24oz. shackle 5/16"  
Safe working load: 2800lbs.

**40-06 US**  
length 9-1/4" width 5-5/8"  
weight 24oz. shackle 5/16"

**25-06 UAB**  
length 6-3/4" width 4"  
weight 10oz. shackle 3/16"

**30-06 UAB**  
length 8-1/2" width 4-1/2"  
weight 14oz. shackle 1/4"

**40-06 UAB**  
length 9-1/2" width 5-5/8"  
weight 20oz. shackle 5/16"

## FIDDLE BLOCKS

WITH

**BECKET,  
CAM CLEAT**

AND

**ADJUSTABLE  
SHACKLE**

### 25-06 UAG

length 6-3/4" width 4"  
weight 10oz. shackle 3/16"

### 30-06 UAG

length 8-1/2" width 4-1/2"  
weight 14oz. shackle 1/4"

### 30-06 UAGE

length 8-1/2" width 4-3/4"  
weight 13oz. shackle 3/16"  
Safe working load: 2000lbs.

### 40-06 UAG

length 9-1/2" width 5-5/8"  
weight 20oz. shackle 5/16"

## FIDDLE BLOCKS

WITH

**CAM CLEAT**

AND

**SNAP SHACKLE**

### 25-07 US

length 6-3/8" width 4"  
weight 13oz. shackle 3/16"

### 30-07 US

length 8-1/2" width 4-1/2"  
weight 16oz. shackle 1/4"

### 25-07 UAB

length 6-3/8" width 4"  
weight 9oz. shackle 3/16"

### 30-07 UAB

length 9-3/8" width 4-1/2"  
weight 15oz. depth 2-1/2"

### 25-07 UAG

length 6-3/8" width 4"  
weight 9oz. shackle 3/16"

### 30-07 UAG

length 9-3/8" width 4-1/2"  
weight 15oz. depth 2-1/2"





# ***FIDDLE BLOCKS***

*WITH*

***BECKET,  
CAM CLEAT***

*AND*

***SNAP SHACKLE***

## ***25-08 US***

length 7-1/4"      width 4"  
weight 13oz.      depth 2-1/2"

## ***30-08 US***

length 9-3/8"      width 4-1/2"  
weight 18oz.      depth 2-1/2"

## ***40-08 US***

length 9-3/4"      width 5-1/2"  
weight 25oz.      depth 2-1/2"

## ***25-08 UAB***

length 7-1/4"      width 4"  
weight 10oz.      depth 2-1/2"

## ***30-08 UAB***

length 9-3/8"      width 4-1/2"  
weight 16oz.      depth 2-1/2"

## ***40-08 UAB***

length 9-3/4"      width 5-1/2"  
weight 20oz.      depth 2-1/2"

## ***25-08 UAG***

length 7-1/4"      width 4"  
weight 10oz.      depth 2-1/2"

## ***30-08 UAG***

length 9-3/8"      width 4-1/2"  
weight 16oz.      depth 2-1/2"

## ***40-08 UAG***

length 9-3/4"      width 5-1/2"  
weight 20oz.      depth 2-1/2"

# SINGLE BLOCKS

WITH

## ADJUSTABLE SHACKLE

### 15-13 US

length 2-1/2" width 1-1/16"  
weight 2oz. shackle 5/32"

### 20-13 US

length 3-5/8" width 1-11/16"  
weight 3oz. shackle 5/32"

### 25-13 US

length 4-1/4" width 2"  
weight 5oz. shackle 3/16"

### 27-13 US

length 5-1/4" width 2-3/8"  
weight 8oz. shackle 3/16"  
Safe working load: 1200lbs.

### 30-13 US

length 5-5/8" width 2-11/16"  
weight 8oz. shackle 1/4"

### 40-13 US

length 6" width 2-7/8"  
weight 11oz. shackle 5/16"

### 50-13 US

length 6-1/4" width 3"  
weight 12oz. shackle 5/16"

### 60-13 US

length 6-3/4" width 3-3/8"  
weight 15oz. shackle 5/16"

### 70-13 US

length 8-1/4" width 4"  
weight 29oz. shackle 3/8"

### 40-13 USHL

length 6-5/8" width 3"  
weight 19oz. shackle 3/8"  
Safe working load: 3500lbs.

### 50-13 USHL

length 6-5/8" width 3"  
weight 21oz. shackle 3/8"  
Safe working load: 4000lbs.

### 60-13 USHL

length 8-1/8" width 3-3/4"  
weight 30oz. shackle 1/2"  
Safe working load: 5000lbs.

### 70-13 USHL

length 8-1/2" width 4-1/2"  
weight 40oz. shackle 1/2"  
Safe working load: 8500lbs.



50-13 US ▶

60-13 US

40-13 US

70-13 US



60-13 USHL



40-13 USHL

50-13 USHL

70-13 USHL



25-13 UAB



27-13 UAB



30-13 UAB



40-13 UAB



50-13 UAB



60-13 UAB



40-13 UABE

60-13 UABE



50-13 UABE



30-13 UABE



25-13 UAG



30-13 UAG



40-13 UAG



50-13 UAG



60-13 UAG

## SINGLE BLOCKS WITH ADJUSTABLE SHACKLE

### 25-13 UAB

length 4-1/4" width 2"  
weight 4oz. shackle 3/16"

### 27-13 UAB

length 5-3/8" width 2-3/8"  
weight 7oz. shackle 3/16"

### 30-13 UAB

length 5-5/8" width 2-11/16"  
weight 7oz. shackle 1/4"

### 40-13 UAB

length 6" width 2-7/8"  
weight 9oz. shackle 5/16"

### 50-13 UAB

length 6-1/4" width 3"  
weight 10oz. shackle 5/16"

### 60-13 UAB

length 7-1/4" width 3-3/4"  
weight 19oz. shackle 5/16"

### 30-13 UABE

length 5-1/2" width 2-1/2"  
weight 10oz. shackle 3/16"  
Safe working load: 2000lbs.

### 40-13 UABE

length 6" width 2-3/4"  
weight 11oz. shackle 1/4"  
Safe working load: 3000lbs.

### 50-13 UABE

length 6-1/4" width 3"  
weight 12oz. shackle 5/16"  
Safe working load: 2000lbs.

### 60-13 UABE

length 7-1/4" width 3-3/4"  
weight 18oz. shackle 1/4"  
Safe working load: 3500lbs.

### 25-13 UAG

length 4-1/4" width 2"  
weight 4oz. shackle 3/16"

### 30-13 UAG

length 5-5/8" width 2-11/16"  
weight 7oz. shackle 1/4"

### 40-13 UAG

length 6" width 2-7/8"  
weight 9oz. shackle 5/16"

### 50-13 UAG

length 6-1/4" width 3"  
weight 10oz. shackle 5/16"

### 60-13 UAG

length 6-7/8" width 3-3/4"  
weight 14oz. shackle 5/16"



# SINGLE BLOCKS

## WITH BECKET AND ADJUSTABLE SHACKLE

### 15-14 US

length 2-3/4" width 1-1/16"  
weight 3oz. shackle 5/32"

### 20-14 US

length 4-1/4" width 1-11/16"  
weight 4oz. shackle 5/32"

### 25-14 US

length 5" width 2"  
weight 6oz. shackle 3/16"

### 27-14 US

length 5" width 2"  
weight 6oz. shackle 3/16"

### 30-14 US

length 6-1/2" width 2-11/16"  
weight 9oz. shackle 1/4"

### 40-14 US

length 7" width 2-11/16"  
weight 13oz. shackle 5/16"

### 50-14 US

length 7-5/8" width 3"  
weight 13oz. shackle 5/16"

### 60-14 US

length 7-7/8" width 3-3/8"  
weight 20oz. shackle 5/16"

### 70-14 US

length 10" width 4-1/8"  
weight 2lb. shackle 3/8"

### 50-14 USHL

length 7-7/8" width 3"  
weight 22oz. shackle 5/16"  
Safe working load: 4000lbs.

### 60-14 USHL

length 9-1/8" width 3-3/4"  
weight 32oz. shackle 1/2"  
Safe working load: 5000lbs.

### 70-14 USHL

length 9-3/4" width 4-1/2"  
weight 43oz. shackle 5/8"  
Safe working load: 8500lbs.

15-14 US

25-14 US

30-14 US

20-14 US

50-14 US

27-14 US

60-14 US

40-14 US

70-14 US

70-14 USHL

60-14 USHL

50-14 USHL



# SINGLE BLOCKS WITH BECKET AND ADJUSTABLE SHACKLE



## 25-14 UAB

length 5" width 2"  
weight 5oz. shackle 3/16"

## 27-14 UAB

length 6-1/2" width 2-11/16"  
weight 7oz. shackle 1/4"

## 30-14 UAB

length 6-1/2" width 2-11/16"  
weight 7oz. shackle 1/4"

## 40-14 UAB

length 7" width 2-11/16"  
weight 10oz. shackle 5/16"

## 50-14 UAB

length 7-5/8" width 3"  
weight 11oz. shackle 5/16"

## 60-14 UAB

length 8" width 3-3/4"  
weight 14oz. shackle 5/16"

## 50-14 UABE

length 7-1/2" width 3"  
weight 14oz. shackle 1/4"  
Safe working load: 3000lbs.

## 30-14 UABE

length 6-1/2" width 2-5/8"  
weight 11oz. shackle 3/16"  
Safe working load: 2000lbs.

## 40-14 UABE

length 7" width 2-3/4"  
weight 12oz. shackle 5/16"  
Safe working load: 2000lbs.

## 25-14 UAG

length 5" width 2"  
weight 5oz. shackle 3/16"

## 30-14 UAG

length 6-1/2" width 2-11/16"  
weight 7oz. shackle 1/4"

## 40-14 UAG

length 7" width 2-11/16"  
weight 10oz. shackle 5/16"

## 50-14 UAG

length 7-5/8" width 3"  
weight 11oz. shackle 5/16"

## 60-14 UAG

length 8" width 3-3/4"  
weight 14oz. shackle 5/16"

# SINGLE BLOCKS WITH SNAP SHACKLE

## 25-15 US

length 5" width 2"  
wt. 6oz. sheave dia. 2"

## 30-15 US

length 6-3/8" width 2-11/16"  
wt. 10oz. sheave dia. 2-1/2"

## 40-15 US

length 6-3/4" width 2-11/16"  
wt. 11oz. sheave dia. 2-1/2"

## 25-15 UAB

length 5" width 2"  
wt. 5oz. sheave dia. 2"

## 30-15 UAB

length 6-3/8" width 2-11/16"  
wt. 8oz. sheave dia. 2-1/2"

## 40-15 UAB

length 6-3/4" width 2-11/16"  
wt. 10oz. sheave dia. 2-1/2"

## 25-15 UAG

length 5" width 2"  
wt. 5oz. sheave dia. 2"

## 30-15 UAG

length 6-3/8" width 2-11/16"  
wt. 8oz. sheave dia. 2-1/2"

## 40-15 UAG

length 6-3/4" width 2-11/16"  
wt. 10oz. sheave dia. 2-1/2"



25-15 US



30-15 US



40-15 US



40-15 UAB



30-15 UAB



25-15 UAB



25-15 UAG



30-15 UAG



40-15 UAG



# ***SINGLE BLOCKS WITH SNAP SHACKLE***



**50-15 US**



**60-15 US**



**50-15 UAB**



**60-15 UAB**



**50-15 UAG**



**60-15 UAG**

**50-15 US**  
length 6-7/8" width 3"  
wt. 12oz. sheave dia. 3"

**60-15 US**  
length 7-7/8" width 4-1/4"  
wt. 18oz. sheave dia. 3-1/4"

**50-15 UAB**  
length 6-7/8" width 3"  
wt. 11oz. sheave dia. 3"

**60-15 UAB**  
length 8" width 3-3/4"  
wt. 15oz. sheave dia. 3-1/4"

**50-15 UAG**  
length 6-3/4" width 3"  
wt. 11oz. sheave dia. 3"

**60-15 UAG**  
length 8" width 3-3/4"  
wt. 15oz. sheave dia. 3-1/4"

# ***SINGLE BLOCKS*** ***WITH*** ***BECKET*** ***AND*** ***SNAP SHACKLE***

## ***25-16 US***

length 5-7/8"      width 2"  
wt. 7oz.      sheave dia. 2"

## ***30-16 US***

length 7-3/8"      width 2-3/4"  
wt. 11oz.      sheave dia. 2-1/2"

## ***40-16 US***

length 7-3/8"      width 2-3/4"  
wt. 12oz.      sheave dia. 2-1/2"

## ***25-16 UAB***

length 5-7/8"      width 2"  
wt. 6oz.      sheave dia. 2"

## ***30-16 UAB***

length 7-3/8"      width 2-3/4"  
wt. 9oz.      sheave dia. 2-1/2"

## ***40-16 UAB***

length 7-3/8"      width 2-3/4"  
wt. 11oz.      sheave dia. 2-1/2"

## ***25-16 UAG***

length 5-7/8"      width 2"  
wt. 6oz.      sheave dia. 2"

## ***30-16 UAG***

length 7-3/8"      width 2-3/4"  
wt. 9oz.      sheave dia. 2-1/2"

## ***40-16 UAG***

length 7-3/8"      width 2-3/4"  
wt. 11oz.      sheave dia. 2-1/2"



***25-16 US***



***30-16 US***



***40-16 US***



***40-16 UAB***



***30-16 UAB***



***25-16 UAB***



***25-16 UAG***



***30-16 UAG***



***40-16 UAG***



# ***SINGLE BLOCKS*** WITH ***BECKET*** AND ***SNAP SHACKLE***



**60-16 US**



**50-16 US**



**50-16 UAB**



**60-16 UAB**



**60-16 UAG**



**50-16 UAG**

**50-16 US**  
length 8-1/8" width 3"  
wt. 15oz. shackle 5/16"

**60-16 US**  
length 9" width 3-1/4"  
wt. 18oz. shackle 5/16"

**50-16 UAB**  
length 8-1/2" width 3"  
wt. 13oz. shackle 5/16"

**60-16 UAB**  
length 9" width 3-1/4"  
wt. 18 oz. sheave dia. 3-1/4"

**50-16 UAG**  
length 8-1/2" width 3"  
wt. 13oz. shackle 5/16"

**60-16 UAG**  
length 9" width 3-1/4"  
wt. 18 oz. sheave dia. 3-1/4"

# DOUBLE BLOCKS

WITH

## ADJUSTABLE SHACKLE

### 15-17 US

length 3"      width 1-1/16"  
weight 3oz.      depth 1-3/8"

### 20-17 US

length 3-5/8"      width 1-11/16"  
weight 6oz.      depth 1-3/8"

### 25-17 US

length 5-1/2"      width 2"  
weight 10oz.      depth 1-3/4"

### 30-17 US

length 6-1/2"      width 2-1/2"  
weight 17oz.      depth 2"

### 40-17 US

length 6-1/2"      width 2-5/8"  
weight 18oz.      depth 2"

### 50-17 US

length 7"      width 3"  
weight 20oz.      depth 2"

### 60-17 US

length 8"      width 3-1/4"  
weight 43oz.      depth 2-1/8"

### 70-17 US

length 9-1/8"      width 4-3/8"  
weight 54oz.      shackle 3/8"

15-17 US



20-17 US



25-17 US



30-17 US ▶



40-17 US ▶



50-17 US ▶



70-17 US



60-17 US



# DOUBLE BLOCKS WITH BECKET AND ADJUSTABLE SHACKLE

## 15-18 US

length 3-1/4" width 1-1/16"  
weight 3oz. depth 1-3/8"

## 20-18 US

length 4-1/4" width 1-11/16"  
weight 6oz. depth 1-3/8"

## 25-18 US

length 6-1/4" width 2"  
weight 11oz. depth 1-3/4"

## 30-18 US

length 7-1/4" width 2-5/8"  
weight 18oz. depth 2"

## 40-18 US

length 7-7/8" width 2-5/8"  
weight 20oz. depth 2"

## 50-18 US


length 9" width 3-5/8"  
weight 36oz. depth 2-1/4"

## 60-18 US

length 9" width 3-5/8"  
weight 36oz. shackle 3/8"

## 70-18 US

length 10-1/2" width 4-1/2"  
weight 56oz. depth 2-1/2"





# TRIPLE BLOCKS

WITH

## ADJUSTABLE SHACKLE

### 15-27 US

length 3"      width 1-1/16"  
weight 4oz.      depth 2"

### 20-27 US

length 4"      width 1-11/16"  
weight 8oz.      depth 2"

### 25-27 US

length 5"      width 2"  
weight 14oz.      shackle 3/16"

### 30-27 US

length 6-1/2"      width 2-3/4"  
weight 23oz.      depth 3"

### 40-27 US

length 6-3/4"      width 2-3/4"  
weight 25oz.      depth 3"

### 50-27 US

length 7"      width 3"  
weight 27oz.      shackle 5/16"

### 60-27 US

length 8"      width 3-3/8"  
weight 40oz.      shackle 3/8"

### 70-27 US

length 9"      width 4-1/4"  
weight 74oz.      depth 4"



15-27 US



20-27 US



25-27 US



30-27 US



40-27 US



50-27 US



60-27 US



70-27 US



# TRIPLE BLOCKS WITH BECKET, AND ADJUSTABLE SHACKLE

## 15-27B US

length 3-1/2" width 1-1/16"  
weight 5oz. depth 2"

## 20-27B US

length 4-3/4" width 1-11/16"  
weight 8oz. shackle 5/32"

## 25-27B US

length 6-1/4" width 2"  
weight 15oz. shackle 3/16"

## 30-27B US

length 7-1/2" width 2-3/4"  
weight 24oz. shackle 1/4"

## 40-27B US

length 7-1/2" width 2-3/4"  
weight 26oz. shackle 5/16"

## 50-27B US


length 8-1/2" width 3"  
weight 35oz. shackle 5/16"

## 60-27B US

length 8-3/4" width 3-1/4"  
weight 41oz. shackle 3/8"

## 70-27B US

length 10-1/2" width 4-1/4"  
weight 77oz. depth 4"



# TRIPLE BLOCKS

WITH  
**BECKET**  
AND  
**CAM CLEAT**  
ADJUSTABLE  
**SHACKLE**

## 25-28 US

length 6-1/4" width 3-3/8"  
weight 19oz. shackle 1/4"

## 30-28 US

length 6-1/2" width 3-1/2"  
weight 20oz. shackle 3/8"

## 40-28 US

length 6-1/2" width 4-1/2"  
weight 21oz. shackle 5/16"

## 50-28 US

length 7-1/4" width 4-1/2"  
weight 32oz. shackle 5/16"

## 60-28 US

length 7-3/4" width 5-1/4"  
weight 34oz. shackle 5/16"



25-28 US



30-28 US



40-28 US



50-28 US



60-28 US



25-13 UB



50-13 UB



60-13 UB



◀ 70-13 UB



◀ 50-14UB



60-14 UB ▶



70-14 UB

## UNIBODY SINGLE BLOCKS

### WITH ADJUSTABLE SHACKLE

#### 25-13 UB

length 3-1/2" width 1-11/16"  
weight 3oz. shackle 3/16"

#### 50-13 UB

length 6-1/4" width 3"  
weight 9oz. shackle 5/16"

#### 60-13 UB

length 7-1/8" width 3-7/8"  
weight 17oz. shackle 5/16"

#### 70-13 UB

length 8-3/4" width 4-3/8"  
weight 34oz. shackle 3/8"

## UNIBODY SINGLE BLOCKS

### WITH BECKET AND ADJUSTABLE SHACKLE

#### 25-14 UB

length 4-3/8" width 1-11/16"  
weight 4oz. shackle 3/16"

#### 50-14 UB

length 7" width 3-1/8"  
weight 12oz. shackle 5/16"

#### 60-14 UB

length 8.5" width 4"  
weight 20oz. shackle 5/16"

#### 70-14 UB

length 10-1/2" width 4-1/2"  
weight 45oz. shackle 3/8"

25-14 UB



# UNIBODY DOUBLE BLOCKS WITH ADJUSTABLE SHACKLE

## 25-17 UB

length 4" width 1-11/16"  
weight 6oz. shackle 3/16"

## 50-17 UB

length 6-1/4" width 2-15/16"  
weight 19oz. shackle 5/16"

## 60-17 UB

length 8" width 4"  
weight 33oz. shackle 5/16"

## 70-17 UB

length 10" width 4-1/2"  
weight 53oz. shackle 3/8"

# UNIBODY DOUBLE BLOCKS WITH BECKET AND ADJUSTABLE SHACKLE

## 25-18 UB

length 4-3/4" width 1-11/16"  
weight 6oz. shackle 3/16"

## 50-18 UB

length 8" width 3"  
weight 20oz. shackle 5/16"

## 60-18 UB

length 9-1/4" width 3-15/16"  
weight 36oz. shackle 5/17"

## 70-18 UB

length 12" width 4-1/2"  
weight 56oz. shackle 3/8"





30SN

40SN

60SN

70SN



Front

Back



MS-SJ



25-31



25-13 USC



## SNATCH BLOCKS

30 SN

length 5" width 2"

weight 8oz.

sheave dia. 1-15/16"

40 SN

length 6-5/8" width 2-3/4"

weight 14oz.

sheave dia. 2-5/8"

60 SN

length 8" width 3-1/2"

weight 21oz.

sheave dia. 3-1/2"

70 SN

length 9-3/8" width 4"

weight 36oz.

sheave dia. 4"

Snatch Blocks come with trunion snap shackle and feature a swivel side plate with pull pin.

## SINGLE BLOCK

WITH

## CAM CLEAT

25-13 USC

length 5" width 2-1/2"

weight 9oz. height 3-3/8"

## SWIVEL JAM

WITH

## DECK MOUNT

MS-SJ

length 6" width 2-1/2"

weight 28oz. height 5-3/8"

optional 25 or 30 series block may be added at an additional cost

## SWIVEL JAM

WITH

## DECK MOUNT

## AND FAIR LEAD

25-31

length 3-3/4" width 2-5/8"

weight 8oz. height 2-3/4"

# BOOM VANGS

## 25-US 4-1

safe working load 1000 lb.  
with 30 ft. of 5/16" line

## 27-US 4-1

safe working load 1000 lb.  
with 30 ft. of 5/16" line

## 30-US 4-1

safe working load 2000 lb.  
with 40 ft. of 3/8" line

## 35-US 4-1

safe working load 2800 lb.  
with 50 ft. of 7/16" line

## 40-US 4-1

safe working load 2800 lb.  
with 50 ft. of 7/16" line

## 25-UAB 4-1

safe working load 1000 lb.  
with 30 ft. of 5/16" line


## 30-UAB 4-1

safe working load 2000 lb.  
with 40 ft. of 3/8" line

## 40-UAB 4-1

safe working load 2800 lb.  
with 50 ft. of 7/16" line


25-US 4-1



27-US 4-1



30-US 4-1



35-US 4-1



40-US 4-1



25-UAB 4-1



30-UAB 4-1



40-UAB 4-1



**25-UAG 4-1**

**30-UAG 4-1**

**30-UAGE 4-1**

**40-UAG 4-1**



## ***BOOM VANGS***

### ***25-UAG 4-1***

safe working load    1000 lb.  
with 30 ft. of 5/16" line

### ***30-UAG 4-1***

safe working load    2000 lb.  
with 40 ft. of 3/8" line

### ***30-UAGE 4-1***

safe working load    2000 lb.  
with 40 ft. of 3/8" line

### ***40-UAG 4-1***

safe working load    2800 lb.  
with 50 ft. of 7/16" line

## ***TWO SPEED VANGS***

### ***40-2SP***

2 speed: 3 to 1 or 6 to 1  
safe working load    2800 lb.  
*Line NOT included*

### ***30-2SP***

2 speed: 3 to 1 or 6 to 1  
safe working load    2000 lb.  
*Line NOT included*

### ***25-2SP***

2 speed: 3 to 1 or 6 to 1  
safe working load    1000 lb.  
*Line NOT included*



**40-2SP**

**30-2SP**

**25-2SP**

# ***HALYARD LIFT BLOCKS***

## ***40-25 SB***

length 3-3/8" width 2-3/8"  
wt. 12oz. sheave dia. 2-1/2"

## ***40-26 SB***

length 3-3/8" width 3"  
weight 17oz. sheave dia. 2-1/8"

## ***30-25 SB***

length 3" width 2-3/8"  
weight 7oz. sheave dia. 1-7/8"

## ***30-26 SB***

length 3" width 2-1/4"  
weight 13oz. sheave dia. 2"

## ***25-25 SB***

length 2-7/8" width 2-1/4"  
weight 11oz. sheave dia. 1-3/4"

## ***25-26 SB***

length 2-7/8" width 2-1/4"  
weight 11oz. sheave dia. 1-3/4"

# ***BOW ROLLERS***

## ***AR-20***

LOA 15-1/2" ID 1-3/4"  
weight 40oz.

## ***AR-20B***

LOA 10-1/2" ID 2"  
weight 44oz.

## ***AR-30***

LOA 24" ID 2-1/2"  
weight 128oz.

## ***AR-35***

LOA 30" ID 2-1/2"  
weight 160oz.

## ***AR-40***

LOA 30" ID 3-1/4"  
weight 208oz.

# ***STEM FITTING***

## ***STM-1***

length 3-1/8" width 1-13/15"  
weight 2oz. height 1-5/16"

# ***STAINLESS HINGE***

## ***HP-1***

length 1-1/2" width 1-1/2"  
weight 1oz.

***40-25 SB***



***40-26 SB***



***30-25 SB***



***30-26 SB***



***25-25 SB***



***25-26 SB***



***AR-20B***




***AR-20***



***AR-40***



***AR-35***



***AR-30***



***STM-1***



***HP-1***






## ROPE CLUTCHES




11-11 A



11-12 S




11-11 S



11-13 S



11-11 B



11-14 S



13-11 S



14-11 S



TAB-1

TAB-1A

### 11-11 A

length 5-7/8" width 1-1/8"  
weight 32oz. height 3"  
use with 5/16" to 9/16" line

### 11-11 B

length 6-1/4" width 1-5/16"  
weight 22oz. height 3-3/4"  
use with 5/16" to 9/16" line

### 11-11 S

length 5-7/8" width 1-1/8"  
weight 32oz. height 3"  
use with 5/16" to 9/16" line

### 11-12 S

length 5-7/8" width 2-1/4"  
weight 48oz. height 3"  
use with 5/16" to 9/16" line

### 11-13 S

length 5-7/8" width 3-3/8"  
weight 72oz. height 3"  
use with 5/16" to 9/16" line

### 11-14 S

length 5-7/8" width 4-1/2"  
weight 80oz. height 3"  
use with 5/16" to 9/16" line

### 13-11 S

length 6" width 1"  
weight 27oz. height 3"  
use with 5/16" to 9/16" line

### 14-11 S

length 6-3/4" width 1"  
weight 30oz. height 3-1/4"  
use with 5/16" to 9/16" line

## TABLE MOUNT

### TAB-1

width 1-11/16" depth 1-1/8"  
weight 2oz. length 2-3/4"

### TAB-1A

width 2" length 3-5/16"  
weight 2oz.

# CHEEK BLOCKS

## 25-24 SB

length 3-1/2" width 2"  
weight 13oz. sheave dia. 2"

## 25-21 SB

length 3-1/2" width 2"  
wt. 7oz. sheave dia. 2"

## 25-23 SB

length 4-5/8" width 2"  
weight 6oz. sheave dia. 2"

## 25-22 SB

length 4-5/8" width 2"  
weight 6oz. sheave dia. 2"

## 30-21 SB

length 3-1/2" width 2-1/2"  
weight 7oz. sheave dia. 2-1/2"

## 30-24 SB

length 3-1/2" width 2-1/2"  
weight 13oz. sheave dia. 2-1/2"

## 40-21 SB

length 3-7/8" width 2-1/2"  
weight 12oz. sheave dia. 2-1/2"

## 40-24 SB

length 3-7/8" width 2-1/2"  
weight 16oz. sheave dia. 2-1/2"

## 45-21 SB

length 5" width 2-3/4"  
weight 16oz. sheave dia. 2-3/4"

## 50-21 SB

length 5" width 3"  
weight 27oz. sheave dia. 3"

## 60-21 SB

length 5" width 3-1/4"  
weight 36oz. sheave dia. 3-1/4"

25-24 SB

25-23 SB



25-21 SB



25-22 SB



40-24 SB



30-21 SB



30-24 SB



40-21 SB



45-21 SB



50-21SB



60-21SB



# DECK ORGANIZERS



30-DO-TB



30-DO-DB



30-DO-QBI



30-DO-DSQB



30-DO-DSTB



30-DO-QB



40-DO-TB




40-DO-DB



40-DO-QBI



40-DO-DSQB



40-DO-DSTB



40-DO-QB

**30-DO-DB**  
length 5-1/8" width 2-1/2"  
wt. 12oz. sheave dia. 2-1/2"

**30-DO-TB**  
length 7-5/8" width 2-1/2"  
wt. 18oz. sheave dia. 2-1/2"

**30-DO-QBI**  
length 10" width 2-1/2"  
wt. 21oz. sheave dia. 2-1/2"

**30-DO-DSQB**  
length 10" width 2-1/2"  
wt. 34oz. sheave dia. 2-1/2"

**30-DO-DSTB**  
length 7-5/8" width 2-1/2"  
wt. 25oz. sheave dia. 2-1/2"

**30-DO-QB**  
length 5-1/8" width 2-1/2"  
wt. 18oz. sheave dia. 2-1/2"

**40-DO-DB**  
length 6-1/4" width 2-1/2"  
wt. 20oz. sheave dia. 2-1/2"

**40-DO-TB**  
length 9-1/8" width 2-1/2"  
wt. 20oz. sheave dia. 2-1/2"

**40-DO-QBI**  
length 12-1/8" width 2-1/2"  
wt. 22oz. sheave dia. 2-1/2"

**40-DO-DSQB**  
length 12-1/4" width 2-1/2"  
wt. 61oz. sheave dia. 2-1/2"

**40-DO-DSTB**  
length 9-1/8" width 2-1/2"  
wt. 46oz. sheave dia. 2-1/2"

**40-DO-QB**  
length 6-1/4" width 2-1/2"  
wt. 33oz. sheave dia. 2-1/2"

# Foot Blocks

## FB-01 SB

length 4-3/8" width 2-1/8"  
bolt dia. 1/4" height 1"  
weight 11oz.

Safe working load: 1200 lbs.

## FB-02 SB

length 5-1/4" width 2-5/8"  
bolt dia. 5/16" height 1-3/16"  
weight 20oz.

Safe working load: 3500 lbs.

## FB-03 SB

length 7" width 3-1/2"  
bolt dia. 3/8" height 1-1/4"  
weight 39oz.

Safe working load: 4000 lbs.

## FB-04 SB

length 8" width 3-3/4"  
bolt dia. 3/8" height 1-3/8"  
weight 51oz.

Safe working load: 4400 lbs.

## FB-05 SB

length 8-3/4" width 4-1/8"  
bolt dia. 1/2" height 1-7/16"  
weight 88oz.

Safe working load: 7500 lbs.

## FB-21 SB

length 4-3/8" width 2-1/8"  
bolt dia. 1/4" height 1-3/4"  
weight 17oz.

Safe working load: 800 lbs./sheave

## FB-22 SB

length 5-1/4" width 2-5/8"  
bolt dia. 1/4" height 2"  
weight 31oz.

Safe working load: 2300 lbs./sheave

## FB-23 SB

length 7" width 3-1/2"  
bolt dia. 3/8" height 2-1/4"  
weight 59oz.

Safe working load: 2650 lbs./sheave

## FB-24 SB

length 8" width 3-3/4"  
bolt dia. 3/8" height 2-1/2"  
weight 78oz.

Safe working load: 2950 lbs./sheave

## FB-25 SB

length 8-3/4" width 4-1/8"  
bolt dia. 1/2" height 5-5/8"  
weight 109oz.

Safe working load: 5000 lbs./sheave

FB-01 SB

FB-03 SB

FB-04 SB

FB-02 SB

FB-05 SB

FB-21 SB

FB-23 SB

FB-22 SB

FB-25 SB

FB-24 SB



## Foot Blocks



**FB-03 NSB**

### **FB-03 NSB**

length 7-3/4" width 3-3/4"  
bolt dia. 3/8" height 1-7/16"  
weight 48oz.  
Safe working load: 4400 lbs.



**FB-06 A**

### **FB-06 A**

length 10" width 6"  
bolt dia. 3/8" height 2-1/2"  
weight 186oz.  
Safe working load: 8500 lbs.


## Clutch Foot Blocks



**SC-26 C**

### **SC-03 C**

length 7" width 3-1/2"  
bolt dia. 3/8" height 1"  
weight 43oz.  
Safe working load: 5600 lbs.



**SC-04 C**

### **SC-04 C**

length 8" width 3-3/4"  
bolt dia. 3/8" height 1-1/8"  
weight 55oz.  
Safe working load: 4400 lbs.



**SC-03 C**

### **SC-23 C**

length 7" width 3-1/2"  
bolt dia. 3/8" height 2-1/8"  
weight 69oz.  
Safe working load: 2650 lbs./sheave



**SC-23 C**

### **SC-24 C**

length 8" width 3-3/4"  
bolt dia. 3/8" height 2-1/8"  
weight 82oz.  
Safe working load: 2900 lbs./sheave



**SC-24 C**

### **SC-26 C**

length 10" width 6"  
bolt dia. 3/8" height 5"  
weight 248oz.  
Safe working load: 5600 lbs./sheave

# ***SINGLE BLOCKS*** ***WITH*** ***SWIVEL*** ***STAND-UP*** ***DECK PLATE***

## ***25-19 US***

length 5"      width 2-1/2"  
wt. 10oz.      sheave dia. 2"

## ***30-19 US***

length 5-1/2"      width 2-3/4"  
wt. 12oz.      sheave dia. 2-1/2"

## ***40-19 US***

length 6"      width 2-3/4"  
wt. 14oz.      sheave dia. 2-1/2"

## ***50-19 US***

length 6-1/8"      width 3"  
wt. 30oz.      sheave dia. 3"

## ***60-19 US***

length 7"      width 3-1/4"  
wt. 26oz.      sheave dia. 3-1/4"

## ***50-19 USHL***

length 6-1/8"      width 3"  
wt. 26oz.      sheave dia. 3"

## ***60-19 USHL***

length 7"      width 3-1/4"  
wt. 31oz.      sheave dia. 3-1/4"

# ***UNIBODY SINGLE*** ***BLOCKS*** ***WITH*** ***SWIVEL*** ***STAND-UP*** ***DECK PLATE***

## ***50-19 UB***

length 5-5/8"      width 1-3/8"  
wt. 13oz      base dia. 2-3/4"  
sheave dia. 3"

## ***60-19 UB***

length 8"      width 1-5/8"  
wt. 22 oz.      base dia. 2-3/4"  
sheave dia. 3-1/4"



***25-19 US***

***30-19 US***

***40-19 US***

***50-19 US***



***60-19 US***

***50-19 USHL***

***60-19 USHL***



***60-19 UB***

***50-19 UB***



# ***SINGLE BLOCKS*** ***WITH*** ***SWIVEL*** ***STAND-UP*** ***DECK PLATE***



**25-19 UAG**



**30-19 UAG**



**40-19 UAG**



**50-19 UAG**



**60-19 UAG**



**60-19 UAB**



**50-19 UAB**



**40-19 UAB**



**30-19 UAB**



**25-19 UAB**

## **25-19 UAG**

length 5" width 2-1/2"  
weight 8oz. sheave dia. 2"

## **30-19 UAG**

length 5-5/8" width 2-3/4"  
wt. 10oz. sheave dia. 2-1/2"

## **40-19 UAG**

length 6" width 2-3/4"  
wt. 12 oz. sheave dia. 2-1/2"

## **50-19 UAG**

length 6" width 3"  
weight 12 oz. sheave dia. 3"

## **60-19 UAG**

length 7" width 3-1/4"  
wt. 20oz. sheave dia. 3-1/4"

## **25-19 UAB**

length 5" width 2-1/2"  
weight 8oz. sheave dia. 2"

## **30-19 UAB**

length 5-5/8" width 2-3/4"  
weight 10oz. sheave dia. 2-1/2"

## **40-19 UAB**

length 6" width 2-3/4"  
wt. 12 oz. sheave dia. 2-1/2"

## **50-19 UAB**

length 6-1/8" width 3"  
weight 19 oz. sheave dia. 3"

## **60-19 UAB**

length 7" width 3-1/4"  
wt. 20 oz. sheave dia. 3-1/4"

# ***SINGLE BLOCKS*** WITH ***BECKET*** AND ***SWIVEL*** ***STAND-UP*** ***DECK PLATE***



**30-20 US ▶**



**25-20 US**  
length 5-1/2" width 2-1/2"  
weight 10oz. sheave dia. 2"

**30-20 US**  
length 6-1/2" width 2-3/4"  
wt. 13oz. sheave dia. 2-1/2"

**40-20 US**  
length 6-3/4" width 2-3/4"  
wt. 15oz. sheave dia. 2-1/2"

**50-20 US**  
length 7-1/8" width 3"  
wt. 18oz. sheave dia. 3"

**60-20 US**  
length 7-7/8" width 3-1/4"  
wt. 24oz. sheave dia. 3-1/4"

**50-20 USHL**  
length 7-1/4" width 3"  
wt. 28oz. sheave dia. 3"

**60-20 USHL**  
length 7-3/4" width 3-1/4"  
wt. 34oz. sheave dia. 3-1/4"



**60-20 US**



**50-20 USHL**

**60-20 USHL**



# SINGLE BLOCKS WITH BECKET AND SWIVEL STAND-UP DECK PLATE



25-20 UAG



30-20 UAG



40-20 UAG



50-20 UAG



◀ 60-20 UAG



60-20 UAB ▶



50-20 UAB



40-20 UAB



30-20 UAB



25-20 UAB

**25-20 UAG**  
length 5-1/2" width 2-1/2"  
wt. 8oz. sheave dia. 2"

**30-20 UAG**  
length 6-1/2" width 2-3/4"  
wt. 10oz. sheave dia. 2-1/2"

**40-20 UAG**  
length 6-3/4" width 2-3/4"  
wt. 12oz. sheave dia. 2-1/2"

**50-20 UAG**  
length 7-1/8" width 3"  
wt. 14oz. sheave dia. 3"

**60-20 UAG**  
length 7-1/2" width 3-1/4"  
wt. 16 oz. sheave dia. 3-1/4"

**25-20 UAB**  
length 5-1/2" width 2-1/2"  
wt. 8oz. sheave dia. 2"

**30-20 UAB**  
length 6-1/2" width 2-3/4"  
wt. 10oz. sheave dia. 2-1/2"

**40-20 UAB**  
length 6-3/4" width 2-3/4"  
wt. 12oz. sheave dia. 2-1/2"

**50-20 UAB**  
length 7-1/8" width 3"  
wt. 14oz. sheave dia. 3"

**60-20 UAB**  
length 7-1/2" width 3-1/4"  
wt. 16oz. sheave dia. 3-1/4"

# MAST PLATES

## MS-1

length 5-1/2" width 3-3/4"  
weight 20oz.

## MS-2

length 5-3/4" width 4-3/4"  
weight 20oz.

## MS-3

length 7" width 4"  
weight 19oz.

## MS-4

length 9-1/2" width 6-1/8"  
weight 36 oz.

## MS-5

length 10-3/8" width 7-3/8"  
weight 40 oz.

## MS-6

length 7-1/2" width 1-1/8"  
weight 8 oz.


*All dimensions for mast plates are measurements of the flat surface of plate making direct contact with deck.*



MS-1




MS-2



MS-3



MS-4



MS-6



MS-5





**EB-3**



**EB-2**



**EB-1**



**30-MH**



**27-MH**



**36-MH**



**40-MH**



**47-MH**



**40-LS MC**



**40-MC**



**30-MC**



**30-LS US**



**JC-3/8**



**JC-1/2**



**60-LS US**

## MAST EXIT BLOCKS

### EB-1

length 2-1/8" width 1-3/8"  
weight 2oz. height 1-7/16"  
sheave dia. 1-1/2"

### EB-2

length 2-1/8" width 1-7/8"  
weight 4oz. height 1-1/16"  
sheave dia. 1-1/2"

### EB-3

length 1-15/16" width 2-5/16"  
weight 6oz. height 1-9/16"  
sheave dia. 1-1/2"

## MAST SHEAVES

### 27-MH

OD 2" ID 5/16"  
weight 2oz. width 3/8"

### 30-MH

OD 2-3/4" ID 1/2"  
weight 3oz. width 9/16"

### 36-MH

OD 3-1/8" ID 1/2"  
weight 5oz. width 11/16"

### 40-MH

OD 3-1/4" ID 7/8"  
weight 6oz. width 9/16"

### 47-MH

OD 4-5/16" ID 3/4"  
weight 13oz. width 13/16"

## MAST BLOCKS

### 30-LS US

length 5-1/4" weight 9oz.

### 30-MC

length 5-1/4" weight 8oz.

### 40-MC

length 5-3/8" weight 8oz.

### 40-LS-MC

length 6-1/2" weight 11oz.

### 60-LS-US

length 6-1/2" weight 15oz.

## JAM CLEATS

### JC-3/8

length 2-1/2" width 1-1/4"  
weight 6 oz. height 2-1/8"

### JC-1/2

length 2-1/2" width 1-1/4"  
weight 6 oz. height 2-1/8"

## BACKSTAY BLOCKS

### TR-R

length 6-1/2" ring dia. 2-3/4"  
wt. 24oz.

(1) large sheave dia. 2-1/2"

(2) small sheave dia. 1-3/4"

### TR-W

length 6-1/2" ring dia. 2-3/4"  
wt. 31oz.

(1) large sheave dia. 2-3/8"

(2) small sheave dia. 1-3/4"



TR-R



TR-W

## STAY ADJUSTERS

### SA-1


height 5/8" width 1/2"  
weight 2oz. length 4-3/4"

### SA-2

height 9/16" width 1/2"  
weight 3oz. length 6-15/16"



SA-1



SA-2

## SHACKLES

### S-1/4

height 1/2" width 1-1/2"  
weight 1oz. length 1-1/2"

### S-5/16

height 11/16" width 1-5/8"  
weight 2oz. length 1-7/16"

### S-3/8


height 13/16" width 2"  
weight 3oz. length 2"

### S-7/16

height 7/8" width 2-3/8"  
weight 6oz. length 2-3/8"



S-1/4



S-7/16



S-3/8



S-5/16

## "D"- SHACKLES

### DS-5/16

height 3/4" width 1-13/16"  
weight 3oz. length 3-1/8"

### DS-1/4

height 3/4" width 1-1/2"  
weight 1-1/2oz. length 2-1/2"

### DS-1/4S

height 1/2" width 1-1/2"  
weight 1oz. length 2"



DS-5/16



DS-1/4



DS-1/4S





## BOOM BALES

### BB-1

width 3"  
weight 2-1/2oz. length 3"

### BB-2

width 3"  
weight 4oz. length 5-1/4"

### BB-3

width 3-7/8"  
weight 5-1/2oz. length 5"

### BB-4

width 4-1/2"  
weight 7oz. length 6"

### BB-5

width 4-3/8"  
weight 6oz. length 6-1/2"

## PRISM POLISH

### PP-1

Prism Polish has been formulated to clean, polish and protect all metals in one application weight 16oz.



PP-1

## BOOM TANGS

### BT-1

width 3"  
weight 1-1/2oz length 3-3/8"

### BT-2

width 2-1/2"  
weight 1oz. length 3-1/4"

## STAY ANCHOR

### SA-3

width 15/16"  
weight 1oz. length 2-7/8"

## EYE STRAPS

### ES-1

height 1/2"  
weight 1/2oz. length 1-5/8"

### ES-2

height 1/2"  
weight 1/2oz. length 2"

### ES-3

height 3/4"  
weight 3/4oz. length 2-1/2"



# ***MAINSHEET TRAVELERS***

*All mainsheet cars and controls are ball bearing construction.*

*Track length and control assembly can be made to suit customer's particular needs.*

## ***MT-1***

Double T-track traveler with double car length

## ***MT-1CT***

Curved double T-track traveler with two cars joined with a coupler.

## ***MT-2***

Standard or heavy-duty track traveler with double car length

## ***MT-2CT***

Standard or heavy-duty curved track traveler with two cars joined with a coupler

## ***MT-2CT-TP***

Standard or heavy-duty curved track traveler with two cars joined with a coupler

## ***MT-3***

Double T-track single car length traveler for boats 25 ft. and under

## ***MT-2-TP***

Standard track traveler with double car length and top control for narrow profile







## ***MAINSHEET TRAVELERS***

***MT-UB-1***  
standard track traveler  
with high strength  
Unibody construction  
for boats 25-32 feet.

***MT-UB-2***  
Heavy-duty track traveler  
with igh strength  
Unibody construction  
for boats 33-42 feet.

***MT-UB-3***  
Heavy-duty or  
super heavy-duty traveler  
for boats 44-60 feet.

## ***UNIVERSAL TRAVELER RISERS***

*Universal Traveler Risers  
are made entirely of welded  
and polished stainless steel,  
and come with back-up plates.*

*Base swivels to conform to  
deck angle. Riser height  
can be reduced to suit  
customer's requirement.*

***UR-1***  
Standard universal riser  
standard height: 9-1/16"  
footprint: 2-1/2"x 6-1/2"  
*Traveler not included,  
sold in pairs*

***UR-2***  
Heavy-duty universal riser  
standard height: 9-5/8"  
footprint: 3"x 6-3/4"  
*Traveler not included,  
sold in pairs*

# ***RIGID BOOM VANGS***

## ***RV12-1***

length: made to order  
tube diameter: 1-1/2"  
boat size: 18-24 ft.

## ***RV20-1 SL***

length: made to order  
tube diameter: 1-3/4"  
boat size: 28-44 ft.  
fittings: custom fitted for  
mast and boom

## ***RV18-1***

length: made to order  
tube diameter: 2"  
boat size: 28-34 ft.  
fittings: custom fitted for  
mast and boom

## ***RV20-1 DX***

length: made to order  
tube diameter: 2"  
boat size: 28-44 ft.  
fittings: custom fitted for  
mast and boom

## ***RV25-1***

length: made to order  
tube diameter: 2-1/4"  
boat size: 45 ft. and up  
fittings: custom fitted for  
mast and boom

***RV12-1***

***RV20-1 SL***

***RV18-1***

***RV20-1 DX***

***RV25-1***





**E-Z G-1UB**



**E-Z G-2UB**



**E-Z G-3**



**SJ-1**  
Optional  
swivel cam on slide



**SJ-2**  
Optional  
swivel cam on slide



**25-40 US**



**30-40 US**



**40-40 US**

## **E-Z GLIDE ADJUSTABLE GENOA CAR SYSTEM**

*Four piece system of 2 control cars and 2 end controls (port and starboard).*

### **E-Z G-1UB**

1" T-track  
safe working load 2000 lb.

### **E-Z G-2UB**

1-1/4" T-track standard duty  
safe working load 2800 lb.

### **E-Z G-3**

1-1/4" T-track heavy duty  
safe working load 3500 lb.

## **E-Z GLIDE SWIVEL CAM**

### **SJ-1**

1" T-track

### **SJ-2**

1-1/4" T-track

## **TRACK CAR SINGLE BLOCKS**

### **25-40 US**

height 4-3/4" width 3"  
weight 10oz. track 1"

### **30-40 US**

height 5-1/2" width 3-1/2"  
weight 12oz. track 1"

### **40-40 US**

height 5-5/8" width 4"  
weight 17oz. track 1-1/4"

# TRACK CAR SINGLE BLOCKS

## 25-40 UAB

height 5-3/16" width 3-1/2"  
weight 12oz. track 1"

## 30-40 UAB

height 6" width 3-1/2"  
weight 15oz. track 1"

## 40-40 UAB

height 6-1/4" width 4"  
weight 21oz. track 1-1/4"

## 25-40 UAG

height 5-3/16" width 3-1/2"  
weight 12oz. track 1"

## 30-40 UAG

height 6" width 3-1/2"  
weight 15oz. track 1"

## 40-40 UAG

height 6-1/4" width 4"  
weight 21oz. track 1-1/4"

## 40-40 UB

height 6-1/2" width 4"  
weight 21oz. track 1-1/4"

## 40-40-SB

height 5-7/8" width 4"  
wt. 20oz. track 1-1/4"

25-40 UAB

30-40 UAB

40-40 UAB



25-40 UAG



30-40 UAG



40-40 UAG



40-40 UB



40-40 SB





**LLC-1**

**LLC-2**

**LLC-3**

**LLC-4**

**LLC-25 US**

## ***Low LEAD CARS***

### ***LLC-1***

track 1"                      weight 15oz.  
length 4-1/4"              height 4-1/4"  
safe working load              2000lb

### ***LLC-2***

track 1, 1-1/4"              wt.32 oz  
length 6"                      height 5"  
safe working load              3000lb.

### ***LLC-3***


track 1-1/4"                      wt.32 oz  
length 6-3/8"              height 5-1/2"  
safe working load              3500 lb.

### ***LLC-4***

track 1-1/2", 1-1/4"              wt. 51oz  
length 8"                      height 6"  
safe working load              4000lb.

### ***LLC-25 US***

track 1"                      weight 10oz.  
length 3-1/4"              height 3-5/8"  
safe working load              1500lb



**TT-1**

**TT-2**

## ***"T"-TRACK***

### ***TT-1***

track width 1"  
sold by the foot

### ***TT-2***

track width 1-1/4"  
sold by the foot

## TRACK CAR SLIDES

### SC-L1

car width fits 1" track  
length 3" width 1-1/4"  
weigh 4oz. height 1-1/4"

### SC-L2

car width fits 1-1/4" track  
length 4" width 1-1/2"  
weigh 8oz. height 1-7/8"

## TRACK CAR ROPE CLUTCH

### 11-11 OC

car width fits 1 or 1-1/4" track  
length 8" width 1-1/8"  
weight 16oz. height 3"  
Line: 5/16" to 9/16"

## TRACK CAR MIDSHIP CLEATS

### MSC-1

car width fits 1" track  
length 7" width 1-3/8"  
weight 10oz. height 2-1/4"

### MSC-2


car width fits 1-1/4" track  
length 8" width 1-1/4"  
weight 13oz. height 2-1/2"

## GENOA TRACK LADDER

### BL-01

Polished stainless steel frame  
with aluminum steps.  
Fits 1 or 1-1/4" T-track

Custom lettering is available  
at an additional charge.



SC-L1



SC-L2



11-11 OC



MSC-1



MSC-2

BL-01



Custom machined lettering  
is available on top ladder step





### stanchion tubes

*Tapered  
tip*



*Flathead  
tip*



*Conehead  
tip*



**standard stanchion  
length is 24-1/2"**

### welded stanchion base styles



**Drawn base  
carriage bolts  
ST-52**



**Drawn base  
flathead screws  
ST-54**



**Flat base  
standard  
ST-58**



**Flat base  
rectangular  
ST-56**

### bases for removable stanchions



**ST-48**



**ST-44**

### stanchion gate styles

**gate brace  
ST-32  
(stanchion not  
included)**



**removable gate  
ST-34**



**Premium  
welded gate  
ST-36**



## **STANCHIONS AND GATES**

Garhauer manufactures a wide variety of stanchions. We offer standard and custom lengths and angles. Just about any combination is available.

### Stanchion tubes available in three different tip styles:

**Tapered tip  
Flathead tip  
Conehead tip**

### Complete stanchions with tube welded to any of these base styles:

- ST-52 - Drawn base carriage bolts**
- ST-54 - Drawn base flathead screws**
- ST-56 - Flat base rectangular**
- ST-58 - Flat base standard**

### Bases for removable stanchion tubes:

- ST-44 - Base for removable stanchion tube standard angle: 0 and 4°**
- ST-48 - Base for removable stanchion tube standard angle: 11 and 19°**

### Gate styles and accessories :

- ST-32 - Gate brace -stanchion not included**
- ST-34 - Standard removable gate**
- ST-36 - Premium welded gate**

## STANCHION BLOCKS

### SB-3

one screw adjustment  
clamps on 1" stanchion  
length 3-3/8" width 2-3/8"  
weight 5oz. height. 11/16"

### SB-4

one screw adjustment  
clamps on 1-1/4" stanchion  
length 5-1/2" width 2"  
weight 10oz. sheave dia. 2"

SB-3



SB-4



SMC-1



## STANCHION SWIVEL BLOCKS

clamps on 1" stanchion  
with two screws

### SB-25

length 3-1/2" width 2-3/8"  
weight 5oz. height 11/16"

### SB-25C

length 6" width 2-5/8"  
weight 11oz. height 3-3/4"



SB-20-13



SB-20-17



SB-25C

## STANCHION SINGLE BLOCK

### SB-20-13

L 4-1/2" W 1-3/4" H 1-1/8"  
weight 6oz. sheave dia. 1-3/4"

## STANCHION DOUBLE BLOCK

### SB-20-17

L 5-1/4" W 1-3/4" H 1-5/8"  
weight 9oz. sheave dia. 1-3/4"



SB-25

## STANCHION MOUNTED CLEAT

### SMC-1


L 7" weight 10oz.  
Fits 1" or 1-1/4" stanchions.

## KAYAK RACKS

### KR-1


Polished stainless steel, a  
stamped plate and four screws  
clamp on the outside of  
stanchions. Sold in pairs

height 20" OD 1"  
width 14" weight 64oz.



KR-1





*Lifting davit*

**LD 6-1**

**LD 6-1M**

## **LIFTING DAVITS**

2-piece stainless steel construction,  
with collapsible arm for easy stowing.  
Comes complete with 60' of line.

**LD 6-1**

height 64"      weight 18lb.  
arm length 26" or 34"  
tubing dia. 2"

**LD 6-1M**

height 64"      weight 17lb.  
arm length 26" or 34"  
tubing dia. 1-3/4"

## **STAINLESS FLAGPOLE STAFF**

**FS-36**

LOA 36"      OD 1"  
Bottom shackle adjustable  
to fit most flag sizes.

## **LOWER BALL MOUNT**

**LBM-1**

height 1-7/8"      width 2-3/4"  
weight 5oz.  
For deck mount of 2" dia. mast

## **UPPER SUPPORT RING**

**USR-1**

height 1-1/2"      width 3-3/4"  
weight 6oz.  
For rail mount of 2" dia. mast

## **OUTBOARD MOTOR LOCK**

**OB-S**

length 8"      width 1-1/4"  
weight 12oz.      height 1-3/4"

**OB-L**

length 11"      width 1-1/4"  
weight 15oz.      height 1-3/4"

## **CARABINER**

**CB-1**

length 4"      width 7/8"  
weight 5oz.      height 2-3/8"

## **RETRACTABLE MOTOR MOUNT**

**OB-125**

Adjusts to two extended and  
one retracted position.  
Capacity is 125 lbs.




**LBM-1**



**USR-1**



**OB-S**



**OB-L**



**CB-1**



**OB-125**

**FS-36**

# RADAR TOWERS

## RT-8

8' deck mounted radar pole  
Available in 2" or 2-1/2" dia.

## RT-10

10' through deck mounted  
radar pole  
Available in 2" or 2-1/2" dia.

RT-8 and RT-10 come complete  
with top plate, pivot or welded  
base, engine hoist and 1" stern  
rail bracket.

Wind generator poles are also  
available.

## RADAR TOWER ACCESSORIES

### Antenna Hoop

Used for mounting additional  
antennas.

### Engine Hoist

Pole mounted engine hoist,  
capacity is 150 lbs.  
arm length 31" or 36"

### Tower Pivot Base

For extreme angles wher stand-  
ard fixed base can't be used,  
with backer plate

### Standoff Bracket

Connects tower to 1" stern rail  
for lateral support. For distance  
of 1-1/2" to 8"

### Tower Strut

Connects tower to deck for lat-  
eral support. Comes complete  
with pivot deck mount, backer  
plate and pole clamp. 1" dia.  
length: made to order

### Strut Pivot Base

with backer plate for deck  
mounting

### Strut Pole Clamp

Connects strut to tower for  
lateral support. Specify pole  
clamp dia.:  
2", 2-3/8", 2-1/2", 3"





## DINGHY DAVITS

### DD 6-1

height 33"      tube dia. 1"  
arm length 36"

### DD 6-2 \*

height 33"      tube dia. 1-1/4"  
arm length 36"

*All davits are made to order, based on the transom design and dimensions of your boat.*

*Sold in pairs, each davit arm is one-piece welded and polished stainless steel construction.*

*Each davit arm comes complete with 6-1 purchase triple block system with cam cleat, snap hook, 60' of line, and cleat for fastening line*

*Included is stainless cross bar cut to length for your particular installation*

*\*not shown*

## DINGHY DAVIT ACCESSORIES

### Davit Pivot Base

For any angle transom mounting of arm, with backer plate.

### Stern Rail Davit Clamp

Clamps davit arm directly to 1" stern rail for lateral support.

DD 6-1

Davit Pivot Base

Stern Rail Davit Clamp

*dinghy not included with davits*

# TURNBUCKLES

Rust-free silicon bronze turnbuckles are machined and chrome plated for the TB-C and TB-CSC series. T-bolts, toggles and clevis pins are stainless steel for long service life. One simple set screw on the polished stainless sleeve allows for periodic inspection.

<b>TB-1C</b>		
pin 5/8"		stud 5/8"
<b>TB-2C</b>		
pin 1/2"		stud 1/2"
<b>TB-3C</b>		
pin 3/8"		stud 3/8"
<b>TB-4C</b>		
pin 5/16"		stud 5/16"
<b>TB-5C</b>		
pin 1/4"		stud 1/4"
<b>TB-1BSC</b>		
pin 5/8"		stud 5/8"
<b>TB-2BSC</b>		
pin 1/2"		stud 1/2"
<b>TB-3BSC</b>		
pin 3/8"		stud 3/8"
<b>TB-4BSC</b>		
pin 5/16"		stud 5/16"
<b>TB-5BSC</b>		
pin 1/4"		stud 1/4"



# PINTLES

**PT-15**  
inside width 7/8" length 4"  
strap width 3/4" pin dia. 3/8"  
weight 4-1/2oz.

**PT-22**  
ins. width 1-1/2" length 4-1/4"  
strap width 1" pin dia. 3/8"  
weight 6oz.

**PT-27**  
inside width 1-5/8" length 5"  
strap-width 1-1/2" pin dia. 1/2"  
weight 14oz.



# GUDGEONS

**GD-15A**  
width 3/4" height 1"  
weight 3oz. length 5-1/8"

**GD-15B**  
width 1" height 1-3/4"  
weight 3oz. length 3"

**GD-27**  
width 1-5/8", height 1-3/4"  
weight 5oz., length 4"





### *Standard Metric Conversion Formulas*

1 inch (1") x 25.4 = 1 millimeter

1 millimeter x .0394 = 1 inch (1")

1 ounce (1oz.) x 28.3495 = 1 gram

1 gram x .0353 = 1 ounce (1oz.)




1 pound (1lb.) x .4536 = 1 kilogram

1 kilogram x 2.2046 = 1 pound(1lb.)

1 foot (1ft.) x .3048 = 1 meter

1 meter x 3.2808 = 1 foot (1ft.)

*GARHAUER'S ADVANCED IN-HOUSE FABRICATION METHODS ASSURE PRODUCTS BUILT WITH ACCURACY AND EFFICIENCY.*





**Garhauer Marine** 1082 West Ninth Street,  
**USA:** Upland, California 91786

Phone: (909) 985-9993  
FAX: (909) 946-3913

email: [garhauer@garhauermarine.com](mailto:garhauer@garhauermarine.com)  
<http://www.garhauermarine.com>

**Garhauer Marine** PO Box 317  
**New Zealand:** Paihia, Bay of Islands

Phone: +64 9 402 6231  
FAX: +64 9 402 6245

email: [sales@garhauer.co.nz](mailto:sales@garhauer.co.nz)  
<http://www.garhauer.co.nz>

